

HGU600T



Full closed-loop control technology, suitable for precision molds & die and precision parts machining.

- + The ability of “0.1 μ Feeding and 1 μ Cutting”, strong anti-vibration performance and less tool wear.
- + Real-time on-machine measurement evaluation and real-time intelligent modification of intermediate machining process.
- + Optionally equipped with laser tool-length calibrator to effectively monitor tool profile, tool wear and spindle thermal elongation.
- + Optionally equipped with $\Phi 150$ high-speed synchronous spindle, cutting ability and machining efficiency are significantly improved, and the composite machining capabilities of milling, grinding, drilling, boring and tapping are strengthened.

HGU600T

Technical Specification

Items		Standard Value
Position Accuracy (X/Y/Z)	mm	0.002/0.002/0.002
Repeatability (X/Y/Z)	mm	0.0018/0.0018/0.0018
Travel (X/Y/Z)	mm	600/500/300
Worktable Size	mm	650×650
Max. Load	Kg	300
Spindle Type		JD150S-20-HA50
Max. Spindle Speed	rpm	20000
Tool Holder Type		HSK-A50
Tool Magazine		Servo Tool Magazine
Tool Magazine Capacity		18
Max. Rapid Rate (X/Y/Z)	m/min	18
Max. Feed Rate (X/Y/Z)	m/min	15
Drive System		AC Servo
Voltage		3-Phase, 380V/50Hz, or Customized
Air Pressure	MPa	≥ 0.52
Machine Weight	Kg	5100

+ Above parameters have been calibrated with reference to International standard ISO230-2.


Standard

- + JD50 Control System
- + Full Closed-loop Control With Grating Scale
- + Spindle & Ball Screw Refrigerator
- + Chain Type Tool Magazine with Manipulator
- + Coolant Tank
- + Contact Tool Calibrator
- + Manual Pulse Generator(MPG)
- + Jingdiao On-machine Measurement System


Optional

- + Coolant Chiller
- + Bag Type Filtration System
- + Probe
- + Spiral Chip Conveyed Coolant Tank
- + Laser Tool Calibrator
- + Oil Mist Separation Device

Machine Dimension



Front View



Left View